



AMI300

Fanless

With Intel® Core™ 2 Duo support



Features

- Mini-ITX system supports IBASE MI910 and MB899 Mini-ITX motherboards
- Available in silver color
- One 2.5" HDD, 5.25" slim type DVD Combo
- Fanless operation
- Optional wall mount kit

AMI300 Specifications

System Mainboard	MI910 & MB899
Construction	Aluminum
Chassis Color	Silver
Front Panel External I/O	Power LED, HDD LED, Reset button, Power on/off button, 2x USB 2.0 ports
Rear Panel External I/O	MI910: audio, 2x LAN, 4x USB, COM, VGA, SPDIF, 1394, KB/MS MB899: audio, 2x LAN, 4x USB, COM, VGA, TV out, SPDIF, 1394, KB/MS
Storage	1x 2.5" HDD, 1x 5.25" slim type DVD combo
Power Supply	80W power adaptor
Mounting	Optional wall mount kit
Dimensions	199mm(W) x 232mm(D) x 77.4mm(H)

Environmental

Operating Temperature	0°C ~ 45°C (32°F ~ 113°F)
Storage Temperature	-20° ~ 80°C
Relative Humidity	5 ~ 90% @ 45°C, non-condensing
Vibration	CFD: 5 grms/5~500Hz random operation HDD: 1g/5~500Hz random operation

Ordering Information

AMI300-8	Aluminum System with MB899EF, Intel® 440 (1.83GHz) CPU, 1GB DDR2, slim DVD COMBO, 2.5" 80GB HDD, 110W DC-DC Converter, 80W Power Adaptor
AMI300-9	Aluminum System with MI910E, Intel® T7500 (2.2GHz) CPU, 2GB DDR2, slim DVD COMBO, 2.5" 80GB HDD, ID392 DVI Board, 110W DC-DC Converter, 80W Power Adaptor
AMI300-BRKT	Wall mount kit for AMI300 series



Remarks: 1. ODM/OEM is available
2. Specifications are subject to change without prior notice.

1 Motherboards

2 Disk-Size SBCs

3 CPU Modules

4 PC/104 Plus

5 CPU Cards

6 AGP & MicroAGP

7 Embedded Systems

8 Network Security Appliance