



## CMI200



### Features

- Mini-ITX system supports IBASE MB899, MB899X & MB896 Mini-ITX motherboards
- Supports extra 2x USB ports
- Available in black color
- LEDs for Standby and Power
- One 2.5" HDD drive bay
- Optional 85W DC power supply
- Optional wall mount kit

### CMI200 Specifications

System Mainboard	MB899, MB899X & MB896
Construction	SECC
Chassis Color	Black
I/O Connectors	MB899/MB899X/MB896 I/O shield, extra 2x USB ports, Standby LED, Power LED, ATX power On/Off/Reset, DC 12V output connectors
Expansion Slots	N/A
Storage	1x 2.5" HDD drive bay
Power Supply	Output Power: DC 60W or 85W (ATX Power) Input Voltage: 115~230VAC (Nom.)
Mounting	Optional wall mount kit
Dimensions	280mm(W) x 200mm(D) x 48mm(H)

### Environmental

Operating Temperature	0°C~ 45°C (32°F~113°F)
Relative Humidity	5 ~ 90% @ 40°C, (non-condensing)

### Ordering Information

CMI200-60	Chassis for Mini-ITX (low power), w/ 60W PSU, 2.5" HDD holder
CMI200-85	Chassis for Mini-ITX (low power), w/ 85W PSU, 2.5" HDD holder
MB899E	Socket 478 for Intel® Core™2 Duo, 945GME Mini-ITX motherboard w/ VGA and 10/100 LAN, 2x COM
MB899EF	Socket 478 for Intel® Core™2 Duo, 945GME Mini-ITX motherboard w/ VGA, 1394, CF, 10/100 and Gigabit LAN, 2x COM
MB899XE	Socket 478 for Intel® Core™2 Duo, 945GME Mini-ITX motherboard w/ VGA and 10/100 LAN, 4x COM
MB899XEF	Socket 478 for Intel® Core™2 Duo, 945GME Mini-ITX motherboard w/ VGA, CF, 10/100 and Gigabit LAN, 4x COM
MB896E	Socket 479 for Pentium® M/Celeron® M, 915GME Mini-ITX motherboard w/ VGA and 10/100 LAN, 2x COM
MB896EF	Socket 479 for Pentium® M/Celeron® M, 915GME Mini-ITX motherboard w/ VGA, 10/100 and Gigabit LAN, 1394, CF, 2x COM
CMI200-BRKT	Wall mount kit for CMI200

Remarks: 1. Use only CPU/heatsink with height fitting the chassis-not touching the chassis top cover.  
2. ODM/OEM is available.