



CMI203



Features

- Mini-ITX system supports iBASE Mini-ITX motherboards
- Available in black color
- Supports 2x PCI slots
- With motherboard's I/O shields and extra 2x USB ports
- LEDs for Standby and Power
- One 3.5" HDD drive bay
- Optional 250W DC power supply
- Optional wall mount kit

CMI203 Specifications

System Mainboard	iBASE Mini-ITX motherboards
Construction	SECC
Chassis Color	Black
I/O Connectors	Flexible iBASE Mini-ITX motherboard's I/O shields, extra 2x USB ports, Standby LED, Power LED, ATX power On/Off/Reset, DC 12V output connectors
Expansion Slots	2x PCI slots
Storage	1x 3.5" HDD drive bay
Power Supply	Output Power: DC 180W or 250W (ATX Power) Input Voltage: 90~264VAC full range
Mounting	Optional wall mount kit
Dimensions	340mm(W) x 225mm(D) x 100mm(H)

Environmental

Operating Temperature	0°C~ 45°C (32°F~113°F)
Relative Humidity	5 ~ 90% @ 40°C, (non-condensing)

Ordering Information

CMI203-180	Chassis for Mini-ITX, w/ 180W PSU, 3.5" HDD holder, 2x PCI-E (optional IP241, IP118-R riser card & iIO LCM)
CMI203-250	Chassis for Mini-ITX, w/ 250W PSU, 3.5" HDD holder, 2x PCI-E (optional IP241, IP118-R riser card & iIO LCM)
MI935	LGA775 Intel® Core™2 Duo Mini-ITX motherboard w/ Intel® Q35 chipset
MI932	Socket AM2 AMD Athlon 64 Mini-ITX motherboard w/ AMD M690E chipset
MI930	AMD Athlon™ 64 / Socket AM2 Mini-ITX motherboard w/ AMD M690T chipset
MI910	Socket 478 Intel® Core™2 Duo Mini-ITX motherboard w/ Intel® GME965 chipset
MI900	LGA775 Intel® Core™2 Duo Mini-ITX motherboard w/ Intel® Q965 chipset
MB899	Socket 478 Intel® Core™2 Duo Mini-ITX motherboard w/ Intel® 945GME chipset
MB899X	Socket 478 Intel® Core™2 Duo Mini-ITX motherboard w/ Intel® 945GME chipset
MB896	Socket 479 Pentium® M/Celeron® M Mini-ITX motherboard w/ Intel® 915GME chipset
MB850	Socket 478 Pentium® 4(M) Mini-ITX motherboard w/ Intel® 845GV chipset
MB770	VIA Eden-V4/C7 Mini-ITX motherboard w/ VIA CN700 chipset
MB740	AMD Geode NX Mini-ITX motherboard/chipset
IP118	Riser card with 1x PCI-E(x16) (see page 24)
IP241-R	Riser card with 2x PCI (see page 24)
CMI203-BRKT	Wall mount kit for CMI203

Remarks: 1. Use only CPU/heatsink with height fitting the chassis-not touching the chassis top cover.
2. ODM/OEM is available.