



## CSB100-520

**Fanless**



### Features

- Supports AMD Geode LX processors (LX700, LX800 or LX900)
- Slim box fanless design for a wide variety of applications
- 1x 10/100BaseT RJ-45 port
- Available in black coating color
- One 2.5" HDD
- DIN rail or optional wall mount kit

### CSB100-520 Specifications

System Mainboard	IB520F
CPU Type	AMD Geode LX800
System Speed	500MHz
Memory	1x DDR SO-DIMM, Max. 1GB
Construction	SECC
Chassis Color	Black
Front Panel External I/O	Front Audio
Rear Panel External I/O	1x USB port, VGA connector, KB/MS connector, 1x COM port, 1x RJ-45 connector, DC-in Jack, 1x PCMCIA socket
Storage	1x 2.5" HDD
Power Supply	60W power adaptor
Mounting	DIN rail or optional wall mount kit
Dimensions	172mm(W) x 114mm(D) x 55mm(H)

### Environmental

Operating Temperature	0°C~60°C (32°F~140°F)
Storage Temperature	-20° ~ 80°C
Relative Humidity	5 ~ 90% @ 45°C, non-condensing
Vibration	CFD: 5 grms/5~500Hz random operation HDD: 1g/5~500Hz random operation

### Ordering Information

CSB100-520	Steel System with IB520F 3.5" SBC AMD Geode LX800 (500MHz) CPU, 1GB DDR, 2.5" 80GB HDD, 60W Power Adaptor
CSB100-520-BRKT	Wall mount kit for CSB100-520



Remarks: 1. ODM/OEM is available  
2. Specifications are subject to change without prior notice.