



## CSB100-530

**Fanless**



### Features

- Supports AMD Geode LX processors (LX700, LX800 or LX900)
- Slim box fanless design for a wide variety of applications
- 2x 10/100BaseT RJ-45 port
- Available in black coating color
- One 2.5" HDD
- DIN rail or optional wall mount kit

Motherboards

1

Disk-Size SBCs

2

CPU Modules

3

PC/104 Plus

4

CPU Cards

5

AGP & MicroAGP

6

Embedded Systems

7

Network Security Appliance

8

### CSB100-530 Specifications

System Mainboard	IB530F
CPU Type	AMD Geode LX800
System Speed	500MHz
Memory	1x DDR SO-DIMM, Max. 1GB
Construction	SECC
Chassis Color	Black
Front Panel External I/O	Power on/off button, 2x USB port, Front Audio
Rear Panel External I/O	2x USB ports, VGA connector, 2x COM ports, 2x RJ-45 connector, DC-in Jack
Storage	1x 2.5" HDD, 1x CF socket
Power Supply	60W power adaptor
Mounting	DIN rail or optional wall mount kit
Dimensions	172mm(W) x 134mm(D) x 55mm(H)

### Environmental

Operating Temperature	0°C~60°C (32°F~140°F)
Storage Temperature	-20° ~ 80°C
Relative Humidity	5 ~ 90% @ 45°C, non-condensing
Vibration	CFD: 5 grms/5~500Hz random operation HDD: 1g/5~500Hz random operation

### Ordering Information

CSB100-530	Steel System with IB530F 3.5" SBC Board, AMD Geode LX800 (500MHz) CPU, 1GB DDR, 2.5" 80GB HDD, 60W Power Adaptor
CSB100-530-BRKT	Wall mount kit for CSB100-530



Remarks: 1. ODM/OEM is available  
2. Specifications are subject to change without prior notice.