



CSB100-881

Fanless



Features

- Supports Intel® Celeron® M 600MHz processors
- Slim box fanless design for a wide variety of applications
- 1x 10/100BaseT RJ-45 port
- 4x USB ports
- Available in black coating color
- One 2.5" HDD & internal CF card (option)
- DIN rail or optional wall mount kit

CSB100-881 Specifications

System Mainboard	IB881
CPU Type	Intel® Celeron® M
System Speed	600MHz
Memory	1x DDR SO-DIMM, Max. 1GB
Construction	SECC
Chassis Color	Black
Front Panel External I/O	1x Power LED, 1x HDD LED, Reset button, Power on/off button, 2x USB port, Front Audio
Rear Panel External I/O	2x USB port, VGA connector, KB/MS connector, 2x COM port, 1x RJ-45 connector, DC-in Jack
Storage	1x 2.5" HDD, optional CF socket
Power Supply	60W power adaptor
Mounting	DIN rail or optional wall mount kit
Dimensions	172mm(W) x114mm(D) x 55mm(H)

Environmental

Operating Temperature	0°C~60°C (32°F~140°F)
Storage Temperature	-20° ~ 80°C
Relative Humidity	5 ~ 90% @ 45°C, non-condensing
Vibration	CFD: 5 grms/5~500Hz random operation HDD: 1g/5~500Hz random operation

Ordering Information

CSB100-881	Steel System with IB881-C6K 3.5" SBC Intel® Celeron® M (600MHz) CPU, 1GB DDR, 2.5" 80GB HDD, 60W Power Adaptor
CSB100-881-BRKT	Wall mount kit for CSB100-881



Remarks: 1. ODM/OEM is available
2. Specifications are subject to change without prior notice.