



Features

- Supports Pentium® 4 / Celeron® processors
Up to 3.06GHz, 400MHz/533MHz FSB
- 2x DDR DIMM, Max. 2GB
- Realtek 8100BL 10/100BaseT LAN
- Integrated VGA for CRT, shared memory
- Watchdog timer, 4x USB 2.0
- 3x PCI slots

System

CPU	Socket 478 for Pentium® 4 / Celeron®, up to 3.06GHz
System Memory	2x DDR DIMM, Max. 2GB
System Chipset	Intel® 845GV + ICH4, 400MHz/533MHz FSB
BIOS	Award
Watchdog Timer	256 levels
SSD	N/A
H/W Monitor	Yes
Expansion Slot	3x PCI

Graphics

VGA Controller	Intel® 845GV integrated VGA for CRT (Intel® Extreme Graphics)
VGA Memory	Intel® DVMT memory allocation
LCD Interface	N/A

LAN

LAN Controller	Realtek 8100BL LAN, 10/100Mbps
Connector	RJ-45 on board

Multi I/O

I/O Chipset	Winbond W83627HF 2x IDE (UDMA33/66/100), 1x FDD, 1x KB, 1x Mouse 2x RS-232, 1x LPT
USB	2 ports on board Pin header for 2 ports (USB 2.0)
Audio	Built-in audio + AC97 codec
Others	IrDA

Mechanical and Environmental

Dimensions	244mm x 244mm (9.6" x 9.6")
Max. Power Requirement	Pentium® 4 2.4GHz w/ 256MB DDR +5V: 0.61A +12V: 5.15A
Operating Temperature	0°C~60°C (32°F~140°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	10%~90% (non-condensing)

Ordering Information

MB840-R	Socket 478 845GV ATX motherboard w/ VGA and 10/100 LAN
---------	--

Remarks:

* Specifications are subject to change without prior notice.