



AMI400 **NEW**

Fanless

With Intel®
Core™2 Duo
support



Features

- Mini-ITX system support iBASE MI910 and MB899 Mini-ITX motherboards
- Available in silver color
- One 2.5" HDD
- One expandable PCI slot
- One 5.25" slim type DVD combo drive (optional)
- Fanless operation
- Optional wall mount kit

Specifications

System Mainboard	MI910 & MB899
Construction	Aluminum & Steel
Chassis Color	Silver
Front Panel External I/O	Power LED, HDD LED, Reset button power on/off button, 2x USB 2.0 ports
Rear Panel External I/O	MI910: audio, 1x LAN, 4x USB, COM, VGA, SPDIF, 1394, KB/MS MB899: audio, 2x LAN, 4x USB, COM, VGA, TV out, SPDIF, 1394, KB/MS
Storage	1x 2.5" HDD, optional 1x 5.25" slim type DVD combo
Expansion Slot	1x PCI
Power Supply	150W power adaptor
Mounting	Optional wall mount kit
Dimensions	267mm(W) x 263.5mm(D) x 109mm(H)

Environmental

Operating Temperature	0°C~ 45°C
Storage Temperature	-20° ~ 80°C
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	CFD: 5 grms/5~500Hz random operation HDD: 0.25 grms/5~500Hz random operation

Ordering Information

AMI400-8	Aluminum System with MB899EF, Intel® 440 (1.83GHz) CPU, 1GB DDR2, 2.5" 80GB HDD, IP115 PCI Riser Card, 110W DC-DC Converter, 150W Power Adaptor
AMI400-9	Aluminum System with MI910E, Intel® T7500 (2.2GHz) CPU, 2GB DDR2, 2.5" 80GB HDD, ID392 DVI Board, IP115 PCI Riser Card, 110W DC-DC Converter, 150W Power Adaptor
AMI400-BRKT	Wall mount kit for AMI400 series



Remarks: 1. Use only CPU/heatsink with height fitting the chassis-not touching the chassis top cover.
2. ODM/OEM is available.
3. Specifications are subject to change without prior notice.