



ASB200-881



Features

- Fanless system supports IBASE IB881 3.5" SBC
- Compact size makes it perfect for portable applications
- Available in silver with blue colors
- One 2.5" HDD
- Rear panel I/O for USB, VGA, KB/MS, COM, LAN and DC-in jack
- Optional wall mount kit

ASB200-881 Specifications

System Mainboard	IB881
CPU Type	Intel® Celeron® M CPU
System Speed	600MHz
Memory	1x DDR SO-DIMM, Max. 1GB
Construction	Aluminum
Chassis Color	Silver enclosure with blue front and rear panels
Front Panel External I/O	Power LED, HDD LED, Reset button, Power on/off button, CF socket
Rear Panel External I/O	2x USB ports, VGA connector, KB/MS connector, COM port, 1x RJ-45 connector, DC-in jack
Storage	1x 2.5" HDD
Power Supply	60W power adaptor
Mounting	Optional wall mount kit
Dimensions	247mm(W) x 213mm(D) x 60mm(H)

Environmental

Operating Temperature	0°C~ 60°C (32°F~140°F)
Storage Temperature	-20° ~ 80°C
Relative Humidity	5~90% @ 40°C, (non-condensing)
Vibration	CFD: 5 grms/5~500Hz random operation HDD: 1g/5~500Hz random operation

Ordering Information

ASB200-881	Aluminum System with IB881-C6K 3.5" SBC, Intel® Celeron® M (600MHz) CPU, 1GB DDR, 2.5" 80GB HDD, 60W Power Adaptor
ASB200-881-BRKT	Wall mount kit for ASB200-881



Remarks: 1. ODM/OEM is available
2. Specifications are subject to change without prior notice.