



ASB200-885 **NEW**



Features

- Fanless system supports IBASE IB885 3.5-inch Disk Size SBC
- Onboard AMD Sempron™ 200U, 1.0GHz
- Available in black color
- Rear panel I/O for USB, DVI, COM (optional VGA), KB/MS, LAN and DC-in jack
- Optional wall mount kit

Specifications

System Mainboard	IB885
CPU Type	AMD Sempron™ 200U, (1.0GHz, DDR2-400, 8W)
System Speed	1.0GHz
Memory	1x DDR2 400 SO-DIMM, Max. 1GB
Construction	Aluminum & Steel
Chassis Color	Black
Front Panel External I/O	Power LED, HDD LED, Power on/off button, Reset button, Audio, 2x USB ports
Rear Panel External I/O	1x DVI, 2x USB ports, 2x RJ45 connectors, 1x VGA (optional COM), KB/MS connector, DC-in jack
Storage	1x 2.5" HDD
Power Supply	80W power adaptor
Mounting	Optional wall mount kit
Dimensions	240mm(W) x 162mm(D) x 37mm(H)

Environmental

Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20° ~ 80°C
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	CFD: 5 grms / 5~500Hz / random operation HDD: 0.25 grms / 5~500Hz / random operation

Ordering Information

ASB200-885-V	Aluminum System with IB885 3.5" SBC, AMD Sempron™ 200U (1.0GHz) CPU, 1GB DDR2, 2.5" 80GB HDD, VGA, 80W Power Adaptor
ASB200-885-S	Aluminum System with IB885 3.5" SBC, AMD Sempron™ 200U (1.0GHz) CPU, 1GB DDR2, 2.5" 80GB HDD, COM, 80W Power Adaptor
ASB200-885-BRKT	Wall mount kit for ASB200-885



Remarks: 1. ODM/OEM is available
2. Specifications are subject to change without prior notice.

1 Motherboards

2 Disk-Size SBCs

3 CPU Modules

4 PC/I/O Plus

5 CPU Cards

6 AGP & MicroAGP

7 Embedded Systems

8 Network Security Appliance