


# IB930



## System

CPU	Socket M Intel® Core™2 Duo / Core™ Duo, up to 2.33GHz
System Memory	1x DDR2 DIMM, Max. 2GB
System Chipset	Mobile Intel® 945GME + ICH7M, 533MHz/667MHz FSB
BIOS	Award
Watchdog Timer	256 levels
SSD	CF socket
H/W Monitor	Yes
Expansion Slot	1x Mini PCI

## Graphics

VGA Controller	Intel® Graphics Media Accelerator (GMA) 950, supports CRT, LVDS
VGA Memory	Max shared memory: 224MB
LCD Interface	Supports 24-bit single or dual channel LVDS

## LAN

LAN Controller	Marvell 88E8053 PCI-E Gigabit LAN
Connector	RJ-45 on board

## Multi I/O

I/O Chipset	ICH7M, Winbond W83627EHG, Fintek F81216 1x IDE (UDMA33/66/100), 1x LPT, 1x KB, 1x Mouse, 4x COM, 2x SATA
USB	1 port on board and 4 ports via pin header (USB 2.0)
Audio	Built-in audio + AC97 codec (ALC655)
Others	ITE IT8888G PCI to ISA bridge (w/o ISA master), IrDA, Digital I/O (4-in/4-out)

## Features

- Supports Intel® Core™2 Duo processors  
Up to 2.33GHz, 667MHz FSB
- 1x DDR2 DIMM, Max. 2GB
- Integrated Intel® 945GME VGA controller supports CRT and LVDS
- Marvell 88E8053 PCI-E Gigabit LAN
- 5x USB 2.0, 4x COM, 2x SATA, 1x Mini PCI
- Watchdog timer, Digital I/O, PCI to ISA bridge

## Mechanical and Environmental

Dimensions	186mm x 129mm (7.32" x 5")
Max. Power Requirement	Core Duo™ 2.33GHz, 667MHz FSB, 1GB DDR2 +5V: 4.03A +12V: 4.33A
Operating Temperature	0°C~60°C (32°F~140°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	10%~90% (non-condensing)

## Ordering Information

IB930H	Socket M Intel® 945GME Half-Size CPU Card w/ VGA and PCI-E Gigabit LAN
--------	--

Remarks:

\* Specifications are subject to change without prior notice.

1 Motherboards

2 Disk-Size SBCs

3 CPU Modules

4 PC/104 Plus

5 CPU Cards

6 AGP & MicroAGP

7 Embedded Systems

8 Network Security Appliance